

compact Pin Busbar, 10mm² connection: 3p/ N (FI N-left) 1x RCCB 4-pole
+ 8x compact device 1 MW touch protected N-left 12 MW cuttable



Model		
product brand name		SETRON
product designation		Pin busbar
design of the product		10 mm², 3p+N, 12MW, RCCB N-Links 3p+N + 8x compact, can be cut
General technical data		
phase number		3
cross-section		10 mm²
operating voltage / rated value / maximum		230 V
Main circuit		
operational current / rated value		63 A
Suitability		
suitability for interaction		
• devices with auxiliary switch		No
• devices with N conductor		Yes
Product details		
product feature / insulated		Yes
Number		
number of devices / suitable for fitting		9
Connections		
type of electrical connection		Pin
Mechanical Design		
height		13.7 mm
width		42.4 mm
length		215.8 mm
net weight		126 g
General Product Approval		Declaration of Conformity
		other

[Miscellaneous](#)



[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3783-0KL>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3783-0KL>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3783-0KL

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



